



**Pipefloats**, an industry standard for the floatation of pipes, hoses and cables for dredging, mining and marine applications.

An easy to install solution that allows pipes to bend and flex, while maintaining low resistance to waves, wind and current.

## Inclusions

**A pipefloat set comprises:**

- 2 pipefloat halves
- A galvanised assembly kit which includes:
  - 4 Rods
  - 8 Nuts
  - 8 Washers

## Specifications

- Manufactured from polyethylene.
- Manufactured in safety orange.
- Stainless steel inserts used in crush areas.
- All floats are pressure tested prior to despatch.
- Recyclable and VOC Free.
- Australian made and designed.
- Specifications are subject to change without notice.

## Stainless Steel Kits

Marine Grade, SAE 316 stainless steel assembly kits for corrosive environments are available at an additional cost.

- Kit includes: 4 Rods, 8 Nuts and 8 Washers.

## Medium Series Pipefloats

PIPE O / D	LENGTH	WEIGHT	RESERVE BUOYANCY
250 mm	1,000 mm	20kg	240 kg
280 mm	1,000 mm	20kg	230 kg
315 mm	1,000 mm	20kg	212 kg
355 mm	1,000 mm	20kg	200 kg

### PIPEFLOAT SPACING GUIDE

**Water** : 4 sets for every 12 meters of pipe  
**Slurry** : 7 sets for every 12 meters of pipe  
eg. 100m Waterpipe: (100m / 12m) x 4 = **33 Floats**

### PACKING GUIDE

### PALLET LOAD

1.2m x 1.2m x 2.20m (height)  
7 Sets per pallet  
Approx Weight 185 kg

\* **RESERVE BUOYANCY** is the weight the float will carry before full submergence.  
\* **O/D** is the Outside Diameter.  
\* Dimensions and weights are nominal.

