




Large Series Pipefloats

PIPE O / D	LENGTH	WEIGHT	RESERVE BUOYANCY
400 mm	1,160 mm	60.0 kg	700 kg
450 mm	1,160 mm	60.0 kg	680 kg
500 mm	1,160 mm	60.0 kg	660 kg
560 mm	1,160 mm	60.0 kg	620 kg
630 mm	1,160 mm	60.0 kg	560 kg

PIPEFLOAT SPACING GUIDE

Water : 4 sets for every 12 meters of pipe
Slurry : 7 sets for every 12 meters of pipe

eg. 100m Waterpipe: (100m / 12m) x 4 = 33 Floats

PACKING GUIDE

PALLET LOAD

1.2m x 1.2m x 2.20 m (height)
 2 Sets per pallet
 Approx Weight 160kg

Pipefloats, an industry standard for the floatation of pipes, hoses and cables for dredging, mining and marine applications.

An easy to install solution that allows pipes to bend and flex, while maintaining low resistance to waves, wind and current.

Inclusions

A pipefloat set comprises:

- 2 pipefloat halves
- A galvanised assembly kit which includes:
 - 4 Rods
 - 8 Nuts
 - 8 Washers

Specifications

- Manufactured from polyethylene.
- Manufactured in safety orange.
- Stainless steel inserts used in crush areas.
- All floats are pressure tested prior to despatch.
- Recyclable and VOC Free.
- Australian made and designed.
- Specifications are subject to change without notice.

Stainless Steel Kits

MarineGrade, SAE316 stainless steel assembly kits for corrosive environments are available at an additional cost.

- Kit includes: 4 Rods, 8 Nuts and 8 Washers.

