




Medium Series Pipefloats

PIPE O / D	LENGTH	WEIGHT	RESERVE BUOYANCY
250 mm	1,000 mm	20 kg	240 kg
280 mm	1,000 mm	20 kg	230 kg
315 mm	1,000 mm	20 kg	212 kg
355 mm	1,000 mm	20 kg	200 kg

PIPEFLOAT SPACING GUIDE

Water : 4 sets for every 12 meters of pipe
Slurry : 7 sets for every 12 meters of pipe
 eg. 100m Waterpipe: (100m / 12m) x 4 = 33 Floats

PACKING GUIDE

PALLET LOAD

1.2m x 1.2m x 2.20 m (height)
 7 Sets per pallet
 Approx Weight 185kg

Pipefloats, an industry standard for the floatation of pipes, hoses and cables for dredging, mining and marine applications.

An easy to install solution that allows pipes to bend and flex, while maintaining low resistance to waves, wind and current.

Inclusions

A pipefloat set comprises:

- 2 pipefloat halves
- A galvanised assembly kit which includes:
 - 4 Rods
 - 8 Nuts
 - 8 Washers


Specifications

- Manufactured from polyethylene.
- Manufactured in safety orange.
- Stainless steel inserts used in crush areas.
- All floats are pressure tested prior to despatch.
- Recyclable and VOC Free.
- Australian made and designed.
- Specifications are subject to change without notice.

Stainless Steel Kits

MarineGrade, SAE316 stainless steel assembly kits for corrosive environments are available at an additional cost.

- Kit includes: 4 Rods, 8 Nuts and 8 Washers.



* RESERVE BUOYANCY is the weight the float will carry before full submergence.

* O/D is the Outside Diameter.

* Dimensions and weights are nominal.

